

BBK PERFORMANCE LLC / For any questions, email us: 3060 Performance Circle / TECH@BBKPERFORMANCE.COM Deland, FL 32724 /

# INSTALLATION INSTRUCTIONS - INS1100/1100A

# AIR FILTER RESTORE KIT

Part # 1100



Special Tools required: None.


Difficulty: Easy.



Install Time: Approximately 30 minutes.



F 🖢 👑 🧿



IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

BBK PERFORMANCE LLC / For any questions, email us: 3060 Performance Circle / TECH@BBKPERFORMANCE.COM Deland, FL 32724 /



# FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION

#### STEP 1

Remove filter from vehicle.

## STEP 2



Wipe large debris from filter. Using the taller white bottle of cleaner from the kit, liberally spray the cleaner until it completely saturates the pleated material.

## STEP 3

Allow cleaner to soak into the filter material for 10 minutes to loosen the dirt. Do not let cleaner dry on filter.

#### STEP 4

Rinse filter with low-pressure water. Apply water from the inside of the filter to the outside. You want the water to carry the dirt away, not work it further into the filter material. Continue to rinse until all the cleaner is gone. If there are spots of dirt remaining, reapply cleaner, let soak and rinse again.

# STEP 5

After final rinsing, gently shake off excess water and allow filter to dry naturally.

Do not proceed to the filter oiling steps until filter is completely dry. Use of any other drying methods (I.E. Compressed air, heat guns) could damage filter.

# STEP 6



For best results, insist on BBK filter oil for your BBK filters. Using the blue filter oil from the kit, apply a bead of oil along the crown of each filter pleat. Work your way around the filter until all pleats are covered.

F E 🖁 🙆

## STEP 7

Wait 20 minutes for the oil to soak into the filter material. Inspect the filter for any lighter colored areas and touch up with a few mores drops of oil. Filter should have a uniform blue color when finished.



#### STEP 8

Reinstall filter onto the vehicle.



IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.



# FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION

## MATERIAL SAFETY DATA SHEET

## **PRODUCT & COMPANY IDENTIFICATION**

Product Name: Air Filter Cleaner MSDS Form: MSDS Issue Date: 3/31/2004 Company: S&B – 787 S. Wanamaker Ave. Ontario, CA 91761 – (909) 947-0015 Emergency ONLY Phone (Chemtrec): (800) 424-9300 International (collect calls accepted): (703) 527-3887

# HAZARDOUS INGREDIENTS

#### **IDENTITY INFORMATION**

Hazardous Components: Sodium Silicate CAS Number(s): 6834920 OSHA PEL: 15MG/M3 ACGIH TLV: 10MG/M3 Weight% (Optional): VOC Content: Note g/L

# PHYSICAL / CHEMICAL CHARACTERISTICS

Flash Point: >212F Specific Gravity: 1.050 Vapor Pressure: Not Tested Melting Point: Not Tested Vapor Density: Not Tested Evaporation Rate: Not Tested Solubility in Water: 100% Appearance & Odor: Clear colorless liquid with mild odor.

# FIRE & EXPLOSION HAZARD DATA

Flash Point: >212F Flammable Limits: Not Tested LEL: Not Established PH: 12 DOT#: n/a NFPA Hazard Rating: H 1 / F 0 / R 0 / S 0 (0-Least, 4-Extreme) HMIS Hazard Rating: H 1 / F 0 / R 0 (0-Least, 4-Extreme) Extinguishing Media: CO2, Dry Foam Special Fire Fighting Procedures: None Unusual Fire & Explosion Hazards: None

# REACTIVITY DATA

Stability: Stable Conditions to Avoid: None Incompatible Materials to Avoid: Strong Oxidizers Hazardous Decomposition or Byproducts: CO, CO2 Hazardous Polymerization: Will not occur Conditions to Avoid: Strong Oxidizers

# HEALTH HAZARD DATA

ROUTES OF ENTRY Inhalation? – Possible Skin? – Possible Ingestion? – Possible Health Hazards: Same as Signs and Symptoms of Exposures Note: All Chemicals in this Product are found on the TSCA Inventory List. OSHA Carcinogenicity? – Note NTP? – None IARC Monographs? – None #04436

F E 🖁 🔘



IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.



# FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION

### HEALTH HAZARD DATA (CONT.)

#### SIGNS AND SYMPTOMS OF OVER EXPOSURE

Eyes: Burning SensationOSkin: Irritant to skin with prolong contactorIngestion: Burning IrritationreInhalation: Not Expected to be a ProblemorMedical Conditions Generally Aggraved by Exposure – Same as Signs andVSymptoms of ExposureLot

#### EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush with Water for 15 Minutes. If Irritation Persists, Call Physician Skin: Wash off with Soap & Water, If Irritation Persists, Call Physician Ingestion: Drink Large Amounts of Water, Call Physician Inhalation: Get Person to Fresh Air, If Unconscious, Call Physician

#### PRECAUTIONS FOR SAFE HANDLING AND USE

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Soak up with inert, absorbent material. Scoop up and place in a proper waste disposal container.

## WASTE DISPOSAL METHOD

Dispose of in accordance with state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store in a cool, dry place, out of direct sunlight. Do not freeze, less than or equal to 32F, or heat above 110F.

#### OTHER PRECAUTIONS

Keep out of reach of children. Follow directions on the container for proper use of this product.

# CONTROL MEASURES

#### RESPIRATORY PROTECTION

Open all doors and windows. If there is an exposure, and it is above the TLV or PEL, a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CRF 1910.134, is required.

#### VENTILATION

Local Exhaust - If Available Special - None Mechanical - If Available Other - None

Protective Gloves: Plastic or Rubber, Chemical Resistant Eye Protection: Glasses, Goggles

Other Protective Clothing or Equipment: None

Work Hygienic Practices: Use common sense and care around chemicals. Never mix chemicals. Consult your supervisor for other practices. All practices depend on your specific business. Directions for use normally found on label which will dictate engineering and control measures.

## OTHER SPECIAL REQUIREMENTS

Note: S&B and BBK believes the data set forth are accurate, S&B and BBK makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion

Prepared by Solaiman Jonatan



IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

