

R-9173/R-9174

5th generation Camaro Seat Track Adaptor Installation Instructions

Warning: The factory seat includes a side impact airbag that many aftermarket seats do not. Disconnecting the airbag, without further modification, will activate an airbag warning light on the cluster to reflect this. This product is intended for off road use only.

Note: Because there are several possible variations of assembly, please read this entire document through before beginning. Doing so will reduce repeated work.

1. Remove stock front seats.

Slide the seat all the way forward and remove the rear torx bolts. Move seat to center position on slider. Lower seat to it's lowest position. Repeat on other seat. Disconnect battery ground cable at the battery. Slightly lift rear of seat and slide the seat backwards, until the front hooks disengage, then tilt the seat forward. Disconnect seat harness, remove seat from car. Repeat on other seat if doing both seats.

Note: Do not disconnect seat harness plugs until battery ground cable is disconnected from car.

2. Assemble aftermarket seat assembly.

Note: many aspects of the aftermarket seat assembly are optional. The order of assembly listed should be followed, but any parts that aren't going on your car can be skipped.

a) Sliders.

The R-9173/4 is designed to optionally be used with Recaro sliders. If sliders are not desired, there are limited positions to bolt the side mount directly to the R-9173/4 (which will allow for a lower seating position, less weight, and a less expensive setup).

Use the included button head bolts (6) and lock nuts (6) to attach the sliders to the seat track adaptors. The button head screws must be used on the bottom, with the nuts on top, to allow the seat track adaptor to be installed in the car when complete. There is only one position on the seat track adaptor where all 3 holes on the slider will line up.

Note: fitment is snug, by design, to eliminate slop once installed.



Move slider forward to allow access to lap belt mount area.

b) Seat belt mounts.

Remove the factory inside seat belt mounts from the factory seat. Remove the clip and bolt from the seat belt mount. Assemble seat belt mounts to seat track adapters:

Install on inboard seat track adapter. If you're using a 4/5/6 point harness, install the inboard clip in lap belt mount, as well (the L shaped one). Depending on your desired seat position, the clip in lap belt mount can be installed above (if you run the seat towards the rear of the slider) or below (if you run your seat towards the front of the slider). Secure lap belt mounts using the included bolt, nylock nut, washer, and reuse the factory washer from the seat belt receiver mount.



The (included) outboard lap belt mount attaches at the same location as the factory outside lap belt, reusing the stock bolt. If you're also using the R-1150 harness bar, there's no need to install this lap belt mount as the functionality is built into the R-1150's downtube base.

C) R-9172 sub strap mount

The R-9173/4 is designed to optionally be used with the R-9172 sub strap mount. The R-9173/4 has multiple forward/rearward locations that can be used, depending on the

position of your seat relative to the seat track adaptor. Some positions require moving the factory wiring harness and/or slightly bending its mounting bracket. The R-9172 bolts in as shown below (sub strap mount below seat track adapter).



D) R-2018 fire extinguisher mount

The R-9173/4 is designed to optionally be used with the R-2018 fire extinguisher mount. The R-2018 fire extinguisher mount goes directly beneath the side mounts, reusing the front mounting bolts on the seat mount. If using a Recaro slider, this means the R-2018 is inserted between the slider and seat mount. The R-2018 comes with spacers for the rear to ensure the side mount is level front and rear.



E) Side mounts. The R-9173/4 seat track adaptors are designed to work with either the R-906X line of side mounts (if using Recaro sliders) or the R-907X and R-975X line of side mounts (if bolting the side mount directly to the seat track adapter). The side mounts you use should be selected by the width of the seat you're installing in the car. Use the hardware included with the side mounts to bolt the side mount to the slider or seat track adapter.

Attach seat to side mount using hardware included with the seat.

Note: because the side mount slider mount holes are slotted, a washer should be used.
Note: Slider centerlines should be 16" apart in order to have the 9173/4 properly align with the floor of the car. Use the slots on the side mounts to adjust until sliders are on 16" centers. To keep seats on the same centerline as stock, adjust both left and right seat mounts equally.

3) Install aftermarket seat assembly in car.

Place steering wheel in upmost and inmost position. Insert seat in car, base first, being cautious not to damage interior trim. The factory seat track to floor hardware is reused to attach the R-9173/4 to the floor. Slot front hooks into floor first, place the included spacer between the rear of the mount and the floor, and then tighten rear factory bolts to the floor. If keeping factory seat belt sensor and lap belt pretensioner, reconnect wiring. Reconnect battery ground cable.

Performance driving events are by nature potentially hazardous to your health. Brey~Krause Mfg. Co. Inc. shall not be liable for injury, consequential, or other types of damages resulting from the use or misuse of our products. Proper installation of these parts is critical and should only be done by a professional shop.