

ROOF RACK INSTALLATION MANUAL



HAVE FUN AND A SAFE RIDE!



www.afxmotorsports.com 4610 Modern Lane, Laredo, TX 78041 Ph. 956-242-6521

THIS PRODUCT IS FOR OFF ROAD USE ONLY

CAN AM X3

CAN006


THANK YOU!

FOR PURCHASING AT AFX MOTORSPORTS



SPORT ROOF RACK

HOW TO INSTALL



Hardware:

(28x) 3/16" x 1/2" Bolts with nuts.

- (20x) 1/4" x 1/2" Bolts with nuts.
 - (6x) 1/4" x 1" Bolts with nuts.

Tools needed (Not Included):


- 5/32" Allen Key.
- 7/16" Combination Wrench.

Liability Statement

AFX Motorsports products are designed to best fit user's ATV/UTV under stock conditions. Adding, modifying, or fabricating any factory or aftermarket parts will void any warranty provided by AFX Motorsports and is not recommended. AFX Motorsports products could interfere with other aftermarket accessories. If user has aftermarket products on machine, contact AFX Motorsports to verify that they will work together. Although AFX Motorsports has thousands of satisfied customers, user should be aware that installing bumpers, rock sliders, spare tire carriers, etc. will change the ride of machine and may increase maintenance and part wear. Operating any off-road machine while, or after, consuming alcohol and/or drugs increases risk of bodily harm or death. No warranty or representation is made as to this product's ability to protect user from severe injury or death. AFX Motorsports products, user agrees that should damages occur, AFX Motorsports will not be held responsible for loss of time, use, labor fees, replacement parts, or freight charges. AFX Motorsports, nor any 3rd party, will not be held responsible for any direct, indirect, indirect, and consequential damages that result from any product purchased from AFX Motorsports. The total liability of seller to user for all damages, losses, and causes of action, if any, shall not exceed the total purchase price paid for the product that gave rise to the claim. AFX Motorsports will warranty only parts provided by AFX Motorsports. Any damage or problems with OEM housings, bearings, seals, or other manufacturers? property, misused, or modified.




To finish with the installation, settle the whole rack over the roof, use six $1/4 \times 1$ " screws with washer and nut (as it is shown in the image).



Install rear frame assembly onto rear side rails (as it is shown in the image). Use four 1/4x 1/2" screws with nut. (Do not tighten yet).

MOTORSPORTS




* For safety tighten all the screws.

7



Align 3 central rails with the perforations (as it is shown in the image). Use twelve 1/4° x 3/4° screws with nut, inserting them bottom-up. (Do no tighten yet)






MOTORSPORTS

3


Install Front frame Assembly onto front side rails (as it is shown in the image). Use four $1/4 \ge 1/2$ screws with nut (Do not tighten yet).

5


Place the rear rack assembly with the front rack assembly, aligning the Bracket #1 with the perforations (as it is shown in the image), using eight $1/4 \ge 1/2$ screws with nut. (Do not tighten yet).



Align 3 central rails with the perforations (as it is shown in the image). Use sixteen 1/4" x 3/4" screws with nut, inserting them bottom-up. (Do not tighten yet).



- Rear Roof Rack Assembly Bracket Direction Align Frontal Roof Rack Assembly Bracket #3 1/4 x 1/2" screw
- Align the last central rail wih the perforations of the Bracket #3 (As it is shown in the image). Use four 3/16 x 3/4" screws with nut, inserting them bottom-up.



Central rail