

## *INSTALLATION GUIDE*

### ***2008-> Audi S5 4.2L Track Edition Exhaust System***

Congratulations on your purchase of the AWE Tuning high performance exhaust for the 2008+ Audi S5 4.2L (Track Edition).

Exquisite build quality with industry leading performance distinguishes this exhaust system from all others.

***Contact us with any installation questions.  
215-658-1670  
AWE-Tuning.com  
performance@AWE-Tuning.com***

## Exhaust System

- 1 front muffler section (part CE)
- 1 driver side rear tubing section (part DE)
- 1 passenger side rear section (part DF)
- 2 Y-Pipe tailpipe section
- 4 63.5mm Accu-Seal clamp (Driver side CJ, Passenger CK)
- 4 2.5" T-bolt clamp
- 4 90mm" slash cut tip (optional finish)
- 2 M8 fender washer
- 1 3/8"-16x1.25" SS bolt
- 1 3/8"-16 SS nut
- 2 3/8" washer
- 1 3/8" lock washer
- 2 hanger post clamp
- 1 9/64" allen wrench (for hanger post clamp)


## Optional Downpipes

- 1 driver side flex section
- 1 passenger side flex section
- 1 driver side tube section
- 1 passenger side tube section
- 6 M8 x 30mm SS bolt
- 6 M8 washer
- 6 M8 copper exhaust nut
- 2 manifold to downpipe gasket
- 2 2.50" exhaust band clamp

## Step 1

Remove stock exhaust components.

**\*\*\*WARNING\*\*\* Do NOT unbolt passenger side hanger fastener at Arrow A in Figure 1 as it also attaches fuel tank to chassis. Remove driver side hanger at Arrow B and slide stock exhaust parts out of passenger side hanger.**



## Step 2

Install AWE Tuning exhaust parts as shown in **Figure 2** below. Refer to the Parts List on page 1. Note that there are several adjustment points on the AWE exhaust to ensure proper fitment. Also note that the factory exhaust hangers are also adjustable with slotted bolt holes to allow further fine tuning.




Figure 2

## Step 3

Each rear tip is rotationally adjustable to ensure that the AWE Tuning logo remains centered when the exhaust is installed, and also length adjustable to suit personal taste.

**When adjusting the length of the tips, make sure that the tip and tailpipe of the muffler overlap at least the width of the clamp (arrow in Figure 3).** *This overlap is very important to ensure that the clamp has enough surface area to tighten down in order to keep the tip from falling off while driving!*

Before removing the factory downpipes, first soak the fasteners in a penetrating oil for several hours to ensure easy removal. Fasteners are included with the optional downpipes to replace the factory parts. Also use a quality anti-seize compound on all fastener threads during re-assembly.

**PLEASE NOTE:** You can identify the AWE Tuning **driver side downpipe** flex section by the presence of the serial badge on it.





Figure 3

## Step 4

Once the exhaust system is properly adjusted, install a hanger post clamp on each of the rear muffler hanger posts, as shown at arrow in **Figure 4**. Slide the clamp onto the hanger post so that it sits snug against the rubber element, and then tighten down with the enclosed allen wrench.

These clamps will keep the exhaust from sliding laterally under usage and will keep the tips properly aligned in the valence openings.

Set final tip rotation, stagger, and overall length, and then tighten their T-bolt clamps.



## ENJOY

Once installed properly, your AWE Tuning high performance exhaust will provide a lifetime of trouble free performance.

Please note that the exhaust volume and sound will settle with usage. 800-1000 miles is typically required to fully break in a new exhaust system.

Periodic cleaning of exhaust tips is necessary to maintain proper finish, especially in areas prone to road salt and caustic deicing solutions.

Do **NOT** use metal polish on our Silver or Diamond Black finish tips. Instead, use a mild soap and water solution periodically to clean the finish.



Any questions or comments,  
please do not hesitate to contact us:

1-888-565-2257  
AWE-Tuning.com  
performance@AWE-Tuning.com



AWE Tuning  
2385C Maryland Road  
Willow Grove, PA 19090  
215-658-1670  
performance@AWE-Tuning.com

Thank you for choosing AWE Tuning as your performance automotive parts supplier. Please remember that a performance car is only as strong as its weakest link. Therefore, it is vital that you maintain your vehicle to factory specifications.

**By installing or using the purchased product, the Consumer accepts this warranty and any specific Manufacturer warranties enclosed.**

## Limited Warranty

The following warranty is valid only in the United States.

The Manufacturer's full warranty applies to all products sold.

Secor Ltd. (AWE Tuning) warrants to the original retail purchaser (Consumer) this product (B8 S5 4.2L Track Edition Exhaust) against manufacturing defects for LIFETIME.

Upon verification of warranty coverage, AWE Tuning will repair or replace the defective product at their discretion, without charge. This is the only remedy the Consumer has for any loss or damage, however arising, due to nonconformity in or defect of the product. This warranty does not cover consequential damage, loss of time or revenues, inconvenience, shipping costs, loss of use of vehicle, damage to the vehicle or components, or other incidental or indirect damage.

All warranties are void if the product was not installed by a certified auto mechanic, improperly serviced, modified, or used in a way not intended by the Manufacturer. Use of product in Motorsports or Racing conditions is grounds for warranty denial. Motorsports and Racing is an inherently abusive operational condition, and it is impossible to warranty for this type of usage.

The Consumer is responsible for ensuring that the product is installed in a safe and proper manner, and should cease usage of the product immediately if an unsafe or improper condition is noted. If an unsafe or improper condition is noted, the Consumer should then immediately contact the facility where the product was installed or AWE Tuning directly.

Please contact the original place of purchase for any warranty claims or explanations of this document.